



OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on September 16, 2015.

Univercol Paints Ltd.
6, Hamelacha Street
P.O. Box 8161
Netanya 42505
Israel
972 9 863 7555

Facility: Netanya, Israel

Trade Designation		Protective (Barrier) Materials		Water Contact Temp	Water Contact Material
		Water Contact Size Restriction			
Coatings - Fittings					
Epoxy phenolic FBE-4 5005/5010/5015/5017	[1]	>= 1/2"		C. HOT	PEC
Coatings - Pipe					
Epoxy phenolic FBE-4 5005/5010/5015/5017	[1]	>= 8"		C. HOT	PEC
Coatings - Pump					
Epoxy phenolic FBE-4 5005/5010/5015/5017	[1]	>= 1/2"		C. HOT	PEC
Coatings - Tank					
Epoxy phenolic FBE-4 5005/5010/5015/5017	[1]	>= 20 gal.		C. HOT	PEC
Coatings - Valve					
Epoxy phenolic FBE-4 5005/5010/5015/5017	[1]	>= 1"		C. HOT	PEC

[1] Colors: Blue
Number of Coats: 1 - 2
Maximum Field Use Dry Film Thickness (in mils): 80 - 100µm (3.15 - 3.93 mils)
Recoat Cure Time and Temperature: 10 minutes at 200°C
Final Cure Time and Temperature: 10 minutes at 200°C
Special Comments: Preheat substrate to 230°C prior to application.